

Visioni



Visioni is a waterborne decorative paint for interiors with soft metallic effect.

Visioni is a single-coat, ready-to-use finish to be applied over a coat of **Decoprimer**.

Visioni is solvent free, easy to apply, suitable for the professional applicator as well as for the DIYer.

COLOR PALETTE

Visioni is available in the base color and can be tinted with our 31 toners.

The **Glitter** effect is obtained by adding to **Visioni** the **Glitter Additive** (120g/4,23oz container in 2,5l/0,66gal).

PREPARATION OF THE SUBSTRATE

For a proper application, the surface has to be completely smooth, dry, without dust or humidity stains.

In case of **NEW SURFACES** as traditional concrete, concrete-based plasters, gypsum and plasterboard, only apply a coat of **Decoprimer**.

In case of **OLD SURFACES** as civil plaster, tempera paint and breathable paint in good conditions, it is necessary to brush the surface before applying a coat of **Decoprimer**.

In case of **OLD SURFACES** presenting incoherent or powdery conditions, or that are coated with wax or soap, it is also necessary to sandpaper the surface before applying a coat of primer **Decoprimer**.

In all above situations, the **Decoprimer** grants proper adhesion and insulation.

APPLICATION CYCLE

PRIMER

Product: **Decoprimer**

Consumption: **25 m²/2,5 l (270 ft²/0,66 US gal) pack** according to the surface

Apply a coat by roller or brush.

FIRST COAT

Product: **Visioni**

Consumption: **20 m²/2,5 l (220 ft²/0,66 US gal) pack**

Eventual coloring:

Pour the quantity of colorant as indicated in the color chart into 2,5 l (0,66 US gal) of **Visioni** and mix until complete blending.

Apply one coat of **Visioni**, pure or previously tinted, by brush, in irregular and crossed strokes over ¼ m² (2-3 ft²) at a time. Then redefine the surface at will with a dry brush.

ENVIRONMENTAL CONDITIONS OF APPLICATION

During application the temperature should be included between +10°C and +30°C, while the relative humidity should be lower than 85%.

STORAGE

The product maintains its properties for a period of 24 months if protected from excessive heat and cold.

Storage temperature should be included between +5°C and +30°C.

Protect from frost.

SAFETY GUIDELINES

Avoid contact with skin and eyes. If contact occurs, rinse thoroughly with water.

Keep away from the reach of children.

For more information consult the safety data sheet.

DISPOSAL

The product must be disposed in agreement with current regulations.

Empty containers should be sent to recycling plants.

TECHNICAL DATA

Packaging	Visioni: 1,25 l (0,33 US gal) - 2,5 l (0,66 US gal) Decoprimer: 2,5 l (0,66 US gal) - 5 l (1,32 US gal) 12,5 l (3,3 US gal) - 15 l (4 US gal) Colorant Additives: 33 ml
Specific weight	Visioni: 1,05 ± 0,05 kg/l Decoprimer: 1,62 ± 0,05 kg/l
pH	Visioni: 7,5 ± 0,05 Decoprimer: 7,5 ± 0,05
Consumption	Visioni: 20 m ² /2,5 l (220 ft ² /0,66 US gal) pack Decoprimer: 25 m ² /2,5 l (270 ft ² /0,66 US gal) pack
Dilution	ready to use
Tools	roller/brush (<i>spalter</i>)
Dry to the touch	2 hours with 20°C room temperature
VOC	Visioni: <5g/l
Dir. 2004/42/CE	Cat. A/l, limit value 2010: 200 g/l Decoprimer: <5 g/l Cat. A/h, limit value 2010: 30 g/l