

KIT EFFETTI DECORATIVI



Coverit has created EFFETTI DECORATIVI, a choice of ten different special atmospheres, which can be realized simply by using one of the 10 available kits. Each kit contains the two products ready-to-use and all that is needed for easy application. The base is VESUVIO but also CARRARA, DUETTO or CALCITE, in natural white or coloured black depending on the kit:

Kit Corten (black base coat col. 2N)
Kit Luna d'Argento (natural white base coat col. 01)
Kit Terra Marina (natural white base coat col. 01)
Kit Luci Polari (natural white base coat col. 01)
Kit Blu Oceano (black base coat col. 2N)
Kit Nero Metropolitan (black base coat col. 2N)
Kit Tramonto Dorato (natural white base coat col. 01)
Kit Notte nel Deserto (natural white base coat col. 01)
Kit Oro Profondo (black base coat col. 2N)
Kit Rosso Marziano (natural white base coat col. 01)

USE

Let the surface dry for at least 48 hours. Shake well before use. Apply the content of bucket no. 1 using the soft sponge found in the kit, proceeding for ½ m² at a time, taking care to remove excess product or dripping using the soft, dry TNT cloth supplied in the kit, until complete absorption.

Let the surface dry for at least 1 hour, then proceed with the application of bucket n. 2 content, shaking well before use, and using the second clean sponge supplied. Always proceed for ½ m² at a time, taking care to remove excess product or dripping using the soft, dry TNT cloth supplied in the kit, until complete absorption

ENVIRONMENTAL CONDITIONS OF APPLICATION

The environmental temperature should not be outside the following range: +5 °C and +30 °C.

STORAGE

The product maintains its properties for a period of 12 months if protected from excessive heat and cold.

Storage temperature should be between +5 °C and +30 °C. **Protect from freezing.**

SAFETY GUIDELINES

Avoid contact with skin and eyes. If contact occurs, rinse thoroughly with water.

Keep out of the reach of children.

For further information consult the Safety Data Sheet.

DISPOSAL

The product must be disposed in accordance with current regulations.

Empty containers should be sent to recycling plants.

TECHNICAL DATA

Packaging	1,25 l + 1,25 l buckets, 2 sponges, 1 TNT pack
Theoretical yield	About 9 m ² per kit
Aspect	Dense liquid
Dry to handle	2 hours with 20 °C room temperature
VOC	Max 1 g/l
Dir. 2004/42/CE	Cat. A/l, limit value 2010: 200 g/l